

SAFETY DATA SHEET

ESTECEM II PASTE A / B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ESTECEM II PASTE A / B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive resin cement. For dental professionals only.

1.3. Details of the supplier of the safety data sheet

Supplier Tokuyama Dental Italy S.r.l.
Via dell'Artigianato, 7,
36030 Montecchio Precalcino, Vicenza, Italy
TEL: +39-0445-334545
FAX: +39-0445-339133

Contact person <http://www.tokuyama-dental.com/tdc/contact.html>

Manufacturer Tokuyama Dental Corporation
38-9, Taitou 1-chome, Taitou-ku, Tokyo
110-0016, Japan
TEL: +81-3-3835-2261
FAX: +81-3-3835-2265

1.4. Emergency telephone number

Emergency telephone Regional Medicines and Poisons Information Centre NI,
Pharmacy Department
Royal Hospital Suite, Grosvenor Road, Belfast
Emergency telephone: 844 892 0111
Telephone: +44 28 90 63 2032
Fax: +44 28 90 24 8030
E-mail address: nirdic.nirdic@belfasttrust.hscni.net

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit . 2 - H 315 : Eye Irrit . 2 - H 319 : Skin Sens . 1 - H 317

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

ESTEC EM II PASTE A / B

Precautionary statements	<p>P261 Avoid breathing vapours.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P501 Dispose of contents/ container in accordance with local regulations.</p>
Contains	<p>(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXY-2,1-ETHANEDIYLOXY-2,1-ETHANEDIYL) BISMETHACRYLATE, 2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] BISMETHACRYLATE</p>
Supplementary precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXY-2,1-ETHANEDIYLOXY-2,1-ETHANEDIYL) BISMETHACRYLATE	10-30%
CAS number: 41637-38-1 EC number: 609-946-4	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
STOT SE 3 - H335	
2,2'-ETHYLENEDIOXYDIETHYL DIMETHACRYLATE	10-30%
CAS number: 109-16-0 EC number: 203-652-6	
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
(1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] BISMETHACRYLATE	1-5%
CAS number: 1565-94-2 EC number: 216-367-7	
Classification	
Skin Sens. 1 - H317	
Aquatic Chronic 3 - H412	

ESTECEM II PASTE A / B

TITANIUM DIOXIDE	<1%
CAS number: 13463-67-7	EC number: 236-675-5
Classification	
Acute Tox. 4 - H332 Carc. 2 - H351	
BENZOYL PEROXIDE	<1%
CAS number: 94-36-0	EC number: 202-327-6
Classification	
Org. Perox. B - H241 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	
2,2'-[(4-METHYLPHENYL)IMINO]BISETHANOL	<1%
CAS number: 3077-12-1	EC number: 221-359-1
Classification	
Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412	
N,N-DIMETHYL-p-TOLUIDINE	<1%
CAS number: 99-97-8	EC number: 202-805-4
Classification	
Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Chronic 3 - H412	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Take off contaminated clothing and wash it before reuse.
Eye contact	Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

ESTEC EM II PASTE A / B

Skin contact Skin irritation. Allergic rash.

Eye contact May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire, toxic gases may be formed.

Hazardous combustion products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Move containers from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. No smoking, sparks, flames or other sources of ignition near spillage.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Keep combustible materials away from spillage. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Use only non-sparking tools.

6.4. Reference to other sections

Reference to other sections For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions All handling should only take place in well-ventilated areas. Keep away from heat, sparks and open flame. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Take any precaution to avoid mixing with combustibles and reducing agents.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from heat, direct sunlight, sparks and open flames. Store in a cool, dark place (0 - 10 °C, 32 - 50 ° F).

7.3. Specific end use(s)

ESTEC EM II PASTE A / B

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): WEL 4 mg/m³ respirable dust

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ inhalable dust

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering controls	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Wear protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station and safety shower. Do not smoke in work area. Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste
Colour	Clear, white to brown
Odour	Characteristic.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Not available.
Flash point	Not applicable.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.

ESTEC EM II PASTE A / B

Vapour density	Not available.
Relative density	Not determined.
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Other information	Not available.
--------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not known.
---	------------

10.4. Conditions to avoid

Conditions to avoid	Keep away from heat, sparks and open flame. Protect against direct sunlight.
----------------------------	--

10.5. Incompatible materials

Materials to avoid	Flammable/combustible materials. Strong reducing agents.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Routes of exposure	Skin , Eyes , Ingestion , Inhalation , Health effects: See section 4.2.
---------------------------	---

Notes (oral LD₅₀)	Not available.
-------------------------------------	----------------

Notes (dermal LD₅₀)	Not available.
---------------------------------------	----------------

Notes (inhalation LC₅₀)	Not available.
---	----------------

Skin corrosion/irritation

Skin corrosion/irritation	Causes skin irritation.
----------------------------------	-------------------------

Animal data	Not available.
--------------------	----------------

Serious eye damage/irritation

ESTECEM II PASTE A / B

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Not available.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity - development Not available.

Specific target organ toxicity - single exposure

STOT - single exposure Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Not available.

SECTION 12: Ecological Information

12.1. Toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

ESTEC EM II PASTE A / B

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General Not regulated.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation (EC) No 1907/2006 (REACH).
(EC) No 1272/2008 (CLP).
(EU) No 2015/830.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to Regulation (EC) 1272/2008 Skin Irrit. 2 - H315: Calculation method. Skin Sens. 1 - H317: Calculation method. Eye Irrit. 2 -H319: Calculation method.

Training advice Ensure operatives are trained to minimise exposure. Only trained personnel should use this material.

Revision comments

Revision date 20/12/2016

ESTECEM II PASTE A / B

Revision	1
Hazard statements in full	H241 Heating may cause a fire or explosion. H301 Toxic if swallowed. H311 Toxic in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.